
Assembly instructions

Oak bench - assembly in 10 steps

Read through the entire guide before you start.



Before you begin

Find a free space

Work on a level floor with space all the way around the bench.

Lay out a blanket

Protects both the floor and the surfaces of the bench from scratches.

Unpack and sort

Lay out all the parts and compare with the parts list on the next page.



Parts and assembly

It's in the package

- A - Trestles, 2 pcs
- B – Side beams (2 pcs.)
- C – Trestle spacer (1 pc.)
- D - Oblique braces (1 pc.)
- E - Slats for the seat

No tools needed

- The bench is assembled completely without tools, glue and screws. The parts hold each other in place.

Check all parts before starting. If something is missing, contact the dealer instead of partially assembling the bench.

Assembly steps 1-2



1

Unpack and lay out the parts

Lay out all the parts: trestles, side beams, spacer, slanting braces and the roller of slats.



2

Assemble the two leg frames

Position the trestles so that the top holes face each other

Assembly steps 3-4



3

Connect the trestles to the spacer

Place the two trestles opposite each other and place the spacer at the bottom. The bench now forms a trestle shape.



4

Fit the diagonal brace

Lower the diagonal brace into place on the trestle and spacer. The bench is now stable - check that it does not wobble.

Assembly steps 5-6



5

Attach the first side bolster

Place a side bolster on top of the trestles.



6

Attach the other side bolster

Repeat with the other side beam. The frame is now rectangular and ready for the seat.

Assembly steps 7-8



7

Put the slatted roller in place

Place the roll of slats on the frame with the straps still on. This keeps the spacing between the slats even.



8

Unfold the slats

Roll out the slats over the frame. Adjust the individual slats at each end so that it locks into the brass stick.

Assembly steps 9-10



9

The bench is ready for use

The bench is now assembled and ready for use



10

When lifting or moving the bench

Flip the slats up at each end and lift the trestles. This will keep the side walls in place.

Maintenance and storage

Wipe with a damp cloth

Use water and possibly a little mild soap. Avoid harsh cleaning agents.

Treat the wood once a year

Sand lightly and give the bench oil or soap so that the oak retains its colour.

Store the bench in a dry place

The bench can be taken apart and laid flat. Store the parts dry and frost-free, with the slats rolled up in their bags.



Contact, spare parts and warranty



Contact the dealer

Write or call the retailer you purchased the product from. Have your order number ready.

Spare parts

Missing or damaged parts will be replaced. Please state the letter of the part from the parts list when ordering.

Warranty

There is a right of complaint for material and manufacturing defects. Normal wear and tear is not covered.

